



China Largest Mining Machinery
Manufacturer

Tel: +86-371-67833161/67833171

MSN Online: hxjq@hxjq.cn

E-mail: sales@hxjq.com sinohxjq@hxjq.com

Yahoo: hongxingmachinery@yahoo.com

Jaw Crusher technical parameters

Model	Feed opening (mm)	Max. feeding size (mm)	Adjusting range of discharge opening (mm)	Processing capacity (t/h)	Rotation speed of eccentric shaft (r/min)	Motor power (kw)	Total weight (t)	Dimensions (L×W×H) (mm)
PE-150×250	150×250	125	10-40	1-3	250	5.5	0.8	720×660×850
PE-200×300	200×300	180	15-50	2-6	260	7.5	1.2	910×750×990
PE-200×350	200×350	180	18-70	3-10	260	11	1.5	1000×870×990
PE-250×400	250×400	210	20-60	5-20	300	15	2.8	1300×1090×1270
PE-400×600	400×600	340	40-100	16-60	275	30	7	1730×1730×1630
PE-500×750	500×750	425	50-100	40-110	275	55	12	1980×2080×1870
PE-600×750	600×750	500	150-200	80-240	275	55	15.8	2070×2000×1920
PE-600×900	600×900	500	65-160	50-180	250	55	17	2190×2206×2300
PE-750×1060	750×1060	630	80-140	110-320	250	110	29	2660×2430×2800
PE-800×1060	800×1060	640	130-190	130-330	250	110	29.8	2710×2430×2800
PE-830×1060	830×1060	650	160-220	150-336	250	110	30.7	2740×2430×2800
PE-870×1060	870×1060	660	200-260	190-336	250	110	31.5	2810×2430×2800
PE-900×1060	900×1060	685	230-290	230-390	250	110	33	2870×2420×2940
PE-900×1200	900×1200	750	95-165	220-450	200	110	52	3380×2870×3330
PE-1000×1200	1000×1200	850	195-265	315-500	200	110	55	3480×2876×3330
PE-1200×1500	1200×1500	1020	150-350	400-800	180	160-220	100.9	4200×3300×3500
PE-1500×1800	1500×1800	1200	220-350	500-1000	180	280-355	122	5160×3660×4248
PE-1600×2100	1600×2100	1500	300-400	1300-2200	160	350-380	150.6	6210×4013×4716
PEX-150×750	150×750	120	18-48	8-25	320	15	3.8	1200×1530×1060
PEX-250×750	250×750	210	25-60	13-35	330	30	5.5	1380×1750×1540
PEX-250×1000	250×1000	210	25-60	16-52	330	30	7	1560×1950×1390
PEX-250×1200	250×1200	210	25-60	20-61	330	37	9.7	2140×1660×1500
PEX-300×1300	300×1300	250	20-90	16-105	300	55	15.6	2720×1950×1600