

MBS Type rod mill technical parameters

Model	Shell Specifications (mm)		Shell rotation speed (r/min)	Feeding size (mm)	Discharging size (mm)	Processing capacity (t/h)	Power (kw)	Total weight (kg)
	Diameter	Length						
MBS0918	900	1800	36-38	≤25	0.833-0.147	0.62-3.2	18.5	5500
MBS0924	900	2400	36	≤25	0.833-0.147	0.81-4.3	22	6100
MBS1224	1200	2400	36	≤25	0.833-0.147	1.1-4.9	30	12000
MBS1530	1500	3000	29.7	≤25	0.833-0.147	2.4-7.5	75	16800
MBS1830	1830	3000	25.4	≤25	0.833-0.147	4.8-11.6	130	29000
MBS2130	2100	3000	23.7	≤25	0.833-0.147	14-35	155	34800
MBS2136	2100	3600	23.7	≤25	0.833-0.147	19-43	180	37000
MBS2430	2400	3000	21	≤50	0.833-0.147	25-65	245	54000
MBS2736	2700	3600	20.7	≤50	0.833-0.147	32-86	380	86000
MBS2740	2700	4000	20.7	≤50	0.833-0.147	32-92	400	94000
MBS3245	3200	4500	18	≤50	0.833-0.147	64-180	630	137000