



China Largest Mining Machinery
Manufacturer

Tel: +86-371-67833161/67833171

MSN Online: hxjq@hxjq.cn

E-mail: sales@hxjq.com sinohxjq@hxjq.com

Yahoo: hongxingmachinery@yahoo.com

High strength pulverizer technical parameters

Type Parameter	High-strength 97	High-strength 93	High-strength 91	High-strength 87	High-strength 76	High-strength 66	High-strength 62
Feeding size (mm)	≤25	≤25	≤25	≤25	≤20	≤15	≤15
Size of finished product (mm)	0.125-0.033	0.125-0.033	0.125-0.033	0.125-0.033	0.125-0.033	0.125-0.044	0.125-0.044
Shift output of different material fineness (t)	4-55	3.5-40	3-36	2.8-33	1.5-25	1-20	0.6-9
Rotate speed of central shaft (r/min)	130	140	148	161	170	190	274
Diameter of pulverizing ring (mm)	1050	1006	973	907.5	850	725	525
Diameter of pulverizing roller (mm)	310	300	300	270	260	210	150
Height of pulverizing roller (mm)	170	160	160	150	150	150	100
Main Motor	Y225S-4-37	Y225M-8-30	Y225M-8-22	Y225M-8-22	Y225S-8-18.5	Y200I-8-15	Y160M-6-7.5
Fan Motor	Y200L-4-37	Y180M-2-22	Y180I-4-22	Y180M-4-18.5	Y160I-4-15	Y160M-4-11	Y132S-4-5.5
Analyzer motor	YC122-4A-5.5	Y112M-6-3	Y112M-6-2.2	Y112M-6-2.2	Y112M-6-2.2	Y112M-6-2.2	Y90I-6-1.1